



Shell Size	A(male)	A(female)	B	C	D
9	0.666"	0.643"	0.984"	1.213"	0.433"
	16.92	16.33	24.99	30.81	11.00
15	0.994	0.971"	1.312"	1.541"	0.433"
	25.25	24.66	33.32	39.14	11.00
25	1.534"	1.511"	1.852"	2.088"	0.433"
	38.96	38.38	47.04	53.04	11.00
37	2.182"	2.159"	2.500"	2.729"	0.433"
	55.42	54.84	63.50	69.32	11.00
50	2.079"	2.064"	2.406"	2.635"	0.433"
	52.81	52.43	61.12	66.93	11.00

Notes:

- Material:
- Insulator - PBT + 30% Glass Fiber (UL94V-0)
 - Contact - Male=Brass, Female=Phosphor Bronze
 - Contact Plating - Gold Flash over Nickel
 - Shell - Tin Plated Steel

- Specification:
- Current Rate - 5 Amp
 - Insul Resist - 1k Mohms
 - Contact Resist - 20Mohm Max.
 - Voltage - 500V AC for 1 minute
 - Op Temp - -40°C to +105°C

RoHS Compliant
as of 11/02/2005

Do not Scale Drawings

Description:		D-Sub, Solder	
Approvals	Date	Phyco 1740-A Junction Ave. San Jose, CA 95112 Drawing# 3150-XX-X (XX=Contact# i.e.09,15,25,37) (X=gender M/F)	
Drawn MAC	3/10 1999		
Checked			
Issued			

PHYco

1740-A Junction Ave
San Jose, CA 95112

Ph. 408-573-9044

Fax. 408-573-9045

November, 2005

PHYCO/JM, Inc.

CERTIFICATE OF COMPLIANCE- RoHS Declaration

For the following Series No's.

3120

3150

3210

Imported By:

Phyco/JM, Inc

1740-A Junction Ave

San Jose, CA 95112

This is to certify that all components used in the above listed Phyco Series' are RoHS compliant and meet the requirements of the current RoHS Directive 2002/95/EC and do not contain above the specified limits of any of the below listed banned substances.

- | | |
|--|-----------------------|
| * Lead | * Hexavalent Chromium |
| * Polybrominated Biphenyls (PBB) | * Mercury |
| * Polybrominated Diphenylethers (PBDE) | * Cadmium |



Jennifer Mahoney
Product Compliance Manager
Phyco/JM, Inc.
408-573-9044
jpapaleo@phyco.com