



**RoHS Compliant
as of 1/30/2006**

Contacts	A	B	C
20	5.08 0.20	15.63 0.62	16.00 0.63
28	7.62 0.30	18.16 0.714	20.57 0.81
32	7.62 0.30	18.16 0.714	22.36 0.88
32k (Rectangle)	^(A1) 7.62 0.30 ^(A2) 10.2 0.40	^(B1) 18.2 0.716 ^(B2) 20.74 0.817	22.36 0.88
44	12.70 0.50	23.20 1.110	27.70 1.09
52	15.24 0.60	25.74 1.01	31.29 1.232
68	20.32 0.80	30.82 1.21	38.48 1.515
84	25.40 1.00	35.90 1.413	45.66 1.800

Notes:

Contact Material: Phosphor Bronze JIS 5210
 Contact Plating: 150u" tin over 40u" nickel
 Insulator: Hi-Temp PPS, UL 94V-0,
 220°C or LCP

Temperature Range: -50°C to +105°C

Current Rating: 1 Amp

Contact Resistance: 30 Milliohms (MAX)

Insulator Resistance: 1k Megohms (MAX)

Withstanding Voltage: AC 600 Vrms

Do not Scale Drawings

Description:

Surface Mount PLCC Socket

Approvals

Date

Drawn

3/10

MAC

1999

Checked

Issued

Phyco

1740-A Junction Ave.

San Jose, CA 95112

Drawing#

4210-(XX)

(XX=Contact #'s 20, 28, 32, 32k, 44, 52, 68, 84)

PHYco

1740-A Junction Ave
San Jose, CA 95112

Ph. 408-573-9044

Fax. 408-573-9045

January, 2006

PHYCO/JM, Inc.

CERTIFICATE OF COMPLIANCE- RoHS Declaration

For the following Series No's.

4140
4160R
4210

Imported By:
Phyco/JM, Inc
1740-A Junction Ave
San Jose, CA 95112

This is to certify that all components used in the above listed Phyco Series' are RoHS compliant and meet the requirements of the current RoHS Directive 2002/95/EC and do not contain above the specified limits of any of the below listed banned substances.

- * Lead
- * Polybrominated Biphenyls (PBB)
- * Polybrominated Diphenylethers (PBDE)
- * Hexavalent Chromium
- * Mercury
- * Cadmium


Jennifer Mahoney
Product Compliance Manager
Phyco/JM, Inc.
408-573-9044
jpapaleo@phyco.com